UNITI®

SPY1500RMi2U

Uniti Power Symphony

The Uniti Power Symphony 1.5kVA UPS series is designed to handle power loads up to 1.5kVA/1.5kW while occupying minimal space, with the ability to switch between rack and tower configurations. Its high power density and advanced double conversion technology make it a reliable solution, further enhanced by its cloud connectivity.



Key Features:

- 1500VA / 1500W
- Unity power factor
- Pure sine wave
- Online double conversion
- Hot swappable batteries
- Small footprint
- High efficiency
- IoT monitoring software
- Easy setup and safe connection to the cloud
- Real-time UPS monitoring to enable business continuity and failure prevention

Peace of mind...

6 YEAR WARRANTY

Uniti Power offers a standard three year warranty on all its UPS systems. This can be extended to an industry first six year UPS warranty when users take advantage of Uniti Power's monitoring support package.

SPY1500RMi2U

Uniti Power Symphony

RATING	1500VA / 1500W
Dimensions W*D*H (mm)	438*445*86.5 (2U)
Weight (kg)	15.5
INPUT	
Voltage tolerance/range	160-300V 100% load, 110-160V derating to 50% load linearly
Frequency	50Hz/60Hz
OUTPUT	
Power factor	1
Waveform	Sine wave
Voltage	200/208/220/230/240V
Frequency	50Hz/60Hz
Efficiency (%)	>95%
Backup time (typical load 0.7)	6 minutes
BATTERY	
DC voltage (VDC)	36V
Maximum EBM quantity	4
MECHANICAL	
Output connection	1 main outlet group (with 4 x IEC C13) 1 programmable outlet group (with 4 x IEC C13)
ENVIRONMENTAL	
Operating temperature tolerance	0-40 °C
Storage temperature tolerance	-15-40 °C
Relative humidity	<0-95% (non-condensing)
Operating altitude tolerance	<1000m

To view the full technical specification please visit www.unitipower.com

1. AC input
2. Battery port
3. 8 x IEC C13
4. Intelligent slot
5. WLAN, USB, RJ45, dry in/out, RS232
6. IoT UPS registration QR code

