



UNITI®



Tempo UPS Series

The Uniti Power Tempo series is a reliable, cost-effective UPS range designed for home working, small offices, retail, and essential IT equipment. With line-interactive technology and built-in voltage regulation (AVR), it delivers stable power and protects against surges, spikes, and outages.

Reliable Power Protection for Everyday Environments

Uniti Power Tempo is designed to safeguard essential devices across home, office and retail settings.



Home Office & Remote Working

- ◆ Modern/Router
- ◆ Desktop PC
- ◆ Monitor
- ◆ Network Storage



Point-of-Sale Systems & Retail

- ◆ POS Terminals
- ◆ Barcode Scanners
- ◆ Receipt Printers
- ◆ Networking Equipment



Security & Connectivity

- ◆ CCTV Cameras
- ◆ Routers
- ◆ Network Switches
- ◆ Access Control Panels

www.unitipower.com

UNITI®

Tempo UPS Series


How Does Uniti Power Tempo Help Protect Your Equipment?

Power Surge Protection



Guards connected devices against voltage spikes and surges, helping prevent damage from storms, mains faults, or poor-quality grid supply.

Stable Voltage Supply with AVR



Integrated Automatic Voltage Regulation corrects minor sags and surges without switching to battery power, reducing wear and extending battery life.

Instant Backup Power



Automatically supplies battery power within milliseconds during a mains failure, giving you time to save work and shut down safely.

Dependable Backup for Essential Continuity

The electronic devices you rely on for work, connectivity, and security need consistent, stable power. Uniti Power Tempo delivers reliable backup and protection to keep you connected when it matters most.



Compact, Versatile Capacity Range

Models from 850VA to 2200VA offer the right solution for single PCs to small network setups, with up to 50 minutes* of runtime for critical shutdowns.



Clear Status at a Glance

Bright LCD display shows real-time operating conditions, battery level, load, and warnings to keep you informed and in control.



USB Connectivity for System Shutdown

USB interface integrates with power management on Windows, Mac, and Linux for automated, safe shutdown during extended outages.



Designed for Real-World Environments

Compact tower design that fits neatly under desks, in offices, retail spaces, or home setups – wherever reliable backup is essential.

**Model dependent.*

UNITI[®] Tempo UPS Series

Uniti Power Tempo Key Features

Reliable Power Protection Made Simple



Sufficient Backup Time

Provides reliable battery support during power cuts, giving you time to save work and shut down safely. Backup times of up to 50 minutes* keep critical equipment running when you need it most.

** Model dependent.*



USB Connectivity for Safe Shutdown

Integrated USB interface enables automated operating system shutdown during extended outages, compatible with Windows, macOS, and Linux power management.



Automatic Voltage Regulation (AVR)

Built-in AVR corrects mains voltage fluctuations without draining the battery, helping to protect your equipment from dips and surges while extending battery life.



Compact, Robust Design

Designed for easy installation in offices, retail spaces, and home setups. A sturdy, compact tower form factor fits neatly under desks or counters.



Surge Protection for Data Lines

RJ11 and RJ45 surge protection options help prevent damage to connected telephone and network equipment from power spikes travelling over data cables.



Comprehensive Model Range

Available in 850VA, 1200VA, and 2200VA capacities to suit a variety of power protection needs, from single workstations to small networks.



Clear LCD Status Display

Easy-to-read LCD panel provides real-time information on UPS status, battery level, load, and fault warnings, keeping you in control at a glance.



6-Year Warranty

Peace of mind with industry-leading coverage for long-term reliability and protection of your investment.

MODEL			
Product Code	TMP850IEC	TMP1200IEC	TMP2200IEC
EAN	7864858535410	7864858532846	7864858528399
INPUT			
Voltage	230 VAC		
Voltage Range	170-280 VAC		
Input Connection	IEC-C14/10A		
OUTPUT			
Capacity	850VA/480W	1200VA/600W	2200VA/1200W
Power Factor	0.56	0.5	0.55
Nominal Voltage	230 VAC		
Voltage Regulation	+/-10% (Battery Mode)		
Frequency Range	50/60Hz		
Frequency Regulation	±1Hz (Battery Mode)		
Waveform	Stepped Sine Wave		
Transfer Time	Typical 2-6ms	Typical 4-8ms	
Output Socket	(3) IEC 10A	(6) IEC 10A	
EFFICIENCY			
Line Mode	95%		
AVR Mode	88%		
Battery Mode	60%		
BATTERY			
Battery Type	12V/9AH	12V/7AH	12V/9AH
Number of Internal Battery	1	2	2
Rated Battery Voltage	12V DC	24V DC	24V DC
Backup Time (est. 100w)	20 min	40 min	50 min
Recharge Time (to 90%)	4 hours to 90% after complete discharge		
SURGE SUPPRESSION			
RJ11 & RJ45 Protection	RJ11	RJ45	
DISPLAY			
LCD	LCD Display		
AUDIBLE ALARM			
Backup Mode	Sounding every 10 seconds		
Low Battery	Sounding every 1 second		
Overload	Sounding every 0.5 second		
Fault	Continuously sounding		
PROTECTION			
Full Protection	Discharge, overcharge and overload protection		
PHYSICAL			
Product Dimensions WxHxD	100 x 143 x 290 mm	139 x 195 x 364 mm	
Packaged Dimensions WxHxD	139 x 226 x 345 mm	236 x 304 x 458 mm	
Product Weight	5.2kg	7.9kg	10.4kg
Packaged Weight	5.4kg	10.0kg	12.0kg
ENVIRONMENT			
Operating Temperature	0°C to 40°C		
Noise Level	<40dB		<45dB
INTERFACE			
USB	Yes		
External Slot	No		
TVSS Protection	Option RJ45		
WARRANTY			
Standard Warranty	6-year parts/1-year batteries		



850VA



1200-2200VA



1200VA



2200VA



Contact Us

We're always happy to help. Contact us via email or telephone on the information below.

 Uniti Power Ltd
21 Orgreave Place, Sheffield,
S13 9LU, UNITED KINGDOM

 info@unitipower.com

 0845 5610 560

 www.unitipower.com